



BEST CON-SLH20

(Industrial liquid Floor Hardener for Dust Proof)



DESCRIPTION:

BEST CON-SLH20 is a Two component liquid dust proof floor hardener coating on industrial floor surface for different color full with dust proof.

Application Area:

BEST CON-SLH20 use for
Industrial Floor area.
Basement Car parking area,
Walk way surface area
All kinds expose surface area.

CHARACTERISTICS / ADVANTAGES

Ready to use: Roller , Brush or spray applied direct from container. Versatile: Equally effective on old or new surfaces. Self-cleaning : Unaffected by salt-laden atmosphere, reduces unsightly staining. Protects brickwork: Risk of efflorescence is reduced. Protects concrete: Reduces causes

APPLICATION INFORMATION:

Consumption 1 kg covers 6-7 m² in 2 coats (depending on the diameter of the rods) 0.120–0.150 kg/m² per coat depending on extent of rusting and nature of substrate. Substrate Temperature +5 °C min. / +50 °C max.

APPLICATION INSTRUCTIONS:

Substrate should be need surface finish, free from oil, dirt and grease. For concrete remove cement skin, loose particles etc. Cavities, pin holes should be levelled.

APPLICATION:

Apply **BEST CON-SLH20** by brush, cotton waste swab or spray on the effected Concrete surface. Leave it in contact with the surface till the reddish color of the corroded surface has changed to nearest original color. Excess application may sometime give whitish black surface. After applied a minimum 24 hours for dry of ceramic surface.

CLEANING OF TOOLS

Wash tools with **BEST CON-SLH20** Cleaner immediately after use. Hardened material can only be removed mechanically

IMPORTANT CONSIDERATIONS:

The surface should be dry before application of **BEST CON-SLH20**. BASIS OF PRODUCT DATA All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.



BEST CON-SLH20



(Industrial liquid Floor Hardener for Dust Proof)

LOCAL RESTRICTIONS:

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Packaging:

BEST CON-SLH20 pack size 30 LTR Set is available .
TYPE A-20 Ltr & TYPE B- 10 Ltr

Consumption:

1 kg covers 6-7 m² in 2 coats (depending on the surface) 0.120–0.150 kg/m² per coat depending on extent of ceramic and nature of substrate.

Estimating Coverage:

Approx. 06 –07 m²/L Note coverage depends on the surface area and the depth of deposition.

Storage Shelf life:

At least 2 year in original sealed containers under normal warehouse conditions. Store properly in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +35 °C.



Best Con

Construction Materials Co; Ltd.

Puchong, Malaysia.

www.bestcon.com.my