



Best Con Mould Release Agent

Economical, general purpose formwork and mould release agent

uses

To assist a positive form release and a smooth defect-free finish, suitable for steel, wood or paper forms.

Advantages

- * Low cost and economical
- * Non staining
- * Minimises form stripping time
- * Maximises life of form work

Description

Best Con Mould Release Agent is a specifically formulated blend based on a light, clear hydrocarbon carrier.

Best Con Mould Release Agent reacts with the free Time in the concrete to produced a soap-like film. The film allows trapped air or free water to escape during vibration to minimise surface voids.

Properties

Colour:	Pale yellow (liquid)
Specification Gravity at 20°C:	0.9

Application

Best Con Mould Release Agent is supplied ready for use. Application by a sprayer is recommended, although brush, roller or swab may also be used

Best Con Mould Release Agent should be applied to forms prior to each use. It can be applied up to a maximum of 2 days prior to pouring. Depending on the environment conditions the drying time is typically 2 - 4 hours.

Best Con Mould Release Agent can be cleaned using diesel or other hydrocarbon solvent.

Supply

Form Release Agent 20 ltr:	FD777002-20L
Form Release Agent 200 ltr:	FD777002-200L
Form Release Agent 1000 ltr (MTO*):	FD777002-1000L

"Made to Order: Min order qty	1
Lead time.	14 - 21 days

Coverage

Non-porous form surfaces	30 - 35 m ² / litre
Semi-porous form surfaces	25 - 30 m ² / litre
Porous form surfaces	12 - 25 m ² / litre

Coverage rate is dependent on the porosity of the form being used. The coverage rate and the form release properres will be reduced if the formwork is a an old/worm nature.

Storage

Protect from frost or prolonged exposure to elevated temperatures.

